State of California Well Completion Report Form DWR 188 Auto-Completed 2/27/2017 WCR2016-006241

Owner's Well Nun	ber D00249	Date Work Began	08/11/2016	Date Work Ended 08/16/2016				
Local Permit Ager	cy Environmental Health Services of M	Ionterey County						
Secondary Permit	Agency	Permit Number	16-12646	Permit Date 04/26/2016				
Well Owner	(must remain confidential p	ursuant to Water	Code 13752)	Planned Use and Activity				
Name XXXXX	xxxxxxxxxxxxxxx	Activity New Well						
Mailing Address	*****			Planned Use Water Supply Irrigation -				
	*****			Agriculture				
City XXXXXXX	xxxxxxxxxxxx	State XX	Zip XXXXX					
		Well Loca	ition					
Address 899 I	ROSITA RD	APN 012-551-006						
City DEL REY	OAKS Zip 93940	County Monte	erey To	Township 15 S				
Latitude	N Longitu	de	VV	ange 01 E				
Deg.	Min. Sec.	Deg. Min.	Sec	action 27 Aseline Meridian Mount Diablo				
Dec. Lat. 36.59	64655 Dec. Lo	ong121.8485616		ound Surface Elevation				
Vertical Datum	Horizontal I	Datum WGS84		levation Accuracy				
Location Accurac	/ Location Determ	Ele	evation Determination Method					
	Borehole Information		Water Le	vel and Yield of Completed Well				
			Depth to first water	(Feet below surface)				
			Depth to Static					
Drilling Method	Direct Rotary Drilling Fluid Be	entonite	Water Level	5 (Feet) Date Measured 08/16/2016				
Total Depth of Bo	ring 130 Fe	et	Estimated Yield*	40 (GPM) Test Type Air Lift				
Total Depth of Co		oot II -	Test Length	2 (Hours) Total Drawdown (feet)				
			May not be represer	ntative of a well's long term yield.				
		Geologic Log -	Free Form					
Depth from Surface			Description					
Feet to Feet			Description					
0 20	Top soil & sand							
20 40	Sand, gravel & sandstone							
40 60	Blue shale & sandstone							
60 100	Black shale							
100 120	Black shale & rock							
120 130	Black shale							

						Casing	s						
			Material			Wall	ess Di	ameter	Screen Type	Slot Size if any (inches)	Descri	ption	
0	60	Blan	k	PVC	OD: 5.563 in. SDR: 21 Thickness: 0.265 in.			5 5	5.563				
60	100	Screen		PVC	OD: 5.563 in. SDR: 21 Thickness: 0.265 in.		0.26	5 5	5.563	Milled Slots	0.032		
100	110	Blan	k	PVC	PVC OD: 5.563 in. SDR: 21 Thickness: 0.265 in.			0.265 5.563					
					Ar	nnular Ma	aterial						
Depth from Surface Feet to Feet		Fill		Fill Type Details			Filter Pack Size		Description				
50	Ceme	ent	10.3 Sa	ck Mix									
130	Filter P	ack	8 x 16										
Borehole Specifications					Certification Statement I, the undersigned, certify that this report is complete and accurate to the best of my knowledge and belief								
Depth from Surface		Borehole Diameter (inches)			I, the undersigned, certify that this report is complete and accurate to the best of my knowledge and belief Name MAGGIORA BROS DRILLING INC								
to Feet		201							MAGG		OS DRILLIN	G INC	
to Feet 130	10.75)	-	Person, F	firm or C	MAGG	on			
-	10.75					-	95 AIRPO	irm or C	MAGG	on	ATSONVILL	E CA	95076 Zip
-	10.75				,	5 Signed	95 AIRPO	Firm or C DRT BL\ ress c signat	MAGG orporati /D ture rec	on W/ ceived		E CA State -	95076 Zip 9957 nse Number
-	10.75				,	5 Signed	595 AIRPO Add electroni	Firm or C DRT BL\ ress c signat	MAGG orporati /D ture rec	on W/ ceived	ATSONVILL City 09/06/201 Date Signe	E CA State -	Zip 9957
-	10.75				,	5 Signed	95 AIRPO Add electroni C-57 Licer	Firm or C DRT BL\ ress c signat	MAGG orporati /D ture rec er Well C	on W/ ceived ontractor /R Use	ATSONVILL City 09/06/201 Date Signe	E CA State -	Zip 9957
-	10.75				,	Signed ,	95 AIRPO Add electroni C-57 Licer	Tirm or C DRT BLV ress c signat	MAGG orporati /D ture rec er Well C DW nber	on w/ ceived ontractor /R Use Sin	ATSONVILL City 09/06/201 Date Signe	E CA State -	Zip 9957 II Number
-	10.75				,	Signed	95 AIRPO Add electroni C-57 Licer	Firm or C DRT BL\ ress c signal ised Wate	MAGG orporati /D ture rec er Well C DW	on W/ ceived ontractor /R Use	ATSONVILL City 09/06/201 Date Signe Only te Code	E CA State -	Zip 9957 II Number
-	10.75				,	Signed	595 AIRPO Add electroni C-57 Licer State V	Firm or C DRT BL\ ress c signal ised Wate	MAGG orporati /D ture rec er Well C DW	on w/ ceived ontractor /R Use Sin	ATSONVILL City 09/06/201 Date Signe Only te Code	E CA State -	Zip 9957 II Number
	Feet to 0 60 100 100 60 100 100 100 130 0 0 0 0 0 0 0 0 0 0 0 0 0	60 100 100 110 100 110 100 Eeet 50 Ceme 130 Filter F Observations: Boreho h from	Feet to Feet Casil 0 60 Blani 60 100 Screet 100 110 Blani 130 Fill Cement 130 Filter Pack Borehole Sp h from	Feet to Feet Casing Type 0 60 Blank 60 100 Screen 100 110 Blank 50 Cement 10.3 Sa 130 Filter Pack 8 x 16 Observations:	Feet to Feet Casing Type Material 0 60 Blank PVC 60 100 Screen PVC 100 110 Blank PVC 100 110 Blank PVC from face to Feet Fill Fill 50 Cement 10.3 Sack Mix 130 Filter Pack 8 x 16 Observations:	Feet to Feet Casing Type Material Casing S 0 60 Blank PVC OD: 5.56 21 Thick in. 60 100 Screen PVC OD: 5.56 60 100 Screen PVC OD: 5.56 21 Thick in. 100 110 Blank PVC OD: 5.56 21 Thick in. 100 110 Blank PVC OD: 5.56 21 Thick in. 100 110 Blank PVC OD: 5.56 21 Thick in. from face Fill Fill Type Detail Screen Ar 50 Cement 10.3 Sack Mix Screen Screen 50 Cement 10.3 Sack Mix Screen Screen Observations: Screen 8 x 16 Screen Screen Borehole Specifications h from Screen Screen Screen Screen	Depth from Surface Feet to Feet Casing Type Material Casings Specificatons 0 60 Blank PVC OD: 5.563 in. SDR: 21 Thickness: 0.265 in. 60 100 Screen PVC OD: 5.563 in. SDR: 21 Thickness: 0.265 in. 100 110 Blank PVC OD: 5.563 in. SDR: 21 Thickness: 0.265 in. 100 110 Blank PVC OD: 5.563 in. SDR: 21 Thickness: 0.265 in. 100 110 Blank PVC OD: 5.563 in. SDR: 21 Thickness: 0.265 in. 50 Cement 10.3 Sack Mix 50 Cement 10.3 Sack Mix 130 Filter Pack 8 x 16 Observations:	Deptn from Surface Feet to Feet Casing Type Material Casings Specificatons Thicknes (inche (inche 0 60 Blank PVC OD: 5.563 in. SDR: 21 Thickness: 0.265 in. 0.26 60 100 Screen PVC OD: 5.563 in. SDR: 21 Thickness: 0.265 in. 0.26 100 110 Blank PVC OD: 5.563 in. SDR: 21 Thickness: 0.265 in. 0.26 100 110 Blank PVC OD: 5.563 in. SDR: 21 Thickness: 0.265 in. 0.26 from face to Feet Fill Fill OD: 5.563 in. SDR: 21 Thickness: 0.265 in. 0.26 50 Cement 10.3 Sack Mix Fill Type Details OD OD 50 Cement 10.3 Sack Mix OD OD OD OD OD OD OD OD Observations: USE USE	Depth from Surface Feet to Feet Casing Type Material Casings Specificatons Wall Thickness (inches) O Di (ii (iii) 0 60 Blank PVC OD: 5.563 in. SDR: 21 Thickness: 0.265 in. 0.265 9 60 100 Screen PVC OD: 5.563 in. SDR: 21 Thickness: 0.265 in. 0.265 9 100 110 Blank PVC OD: 5.563 in. SDR: 21 Thickness: 0.265 in. 0.265 9 100 110 Blank PVC OD: 5.563 in. SDR: 21 Thickness: 0.265 in. 0.265 9 from face to Feet Fill FVC OD: 5.563 in. SDR: 21 Thickness: 0.265 0.265 9 50 Cement 10.3 Sack Mix Fill Type Details Filt 50 Cement 10.3 Sack Mix Image: State of the state	Depth from Surface Feet to Feet Casing Type Material Casings Specificatons Wall Thickness (inches) Outside Diameter (inches) 0 60 Blank PVC OD: 5.563 in. SDR: 21 Thickness: 0.265 in. 0.265 5.563 60 100 Screen PVC OD: 5.563 in. SDR: 21 Thickness: 0.265 in. 0.265 5.563 100 110 Blank PVC OD: 5.563 in. SDR: 21 Thickness: 0.265 in. 0.265 5.563 100 110 Blank PVC OD: 5.563 in. SDR: 21 Thickness: 0.265 in. 0.265 5.563 100 110 Blank PVC OD: 5.563 in. SDR: 21 Thickness: 0.265 in. 0.265 5.563 0 Feet Fill Fill Type Details Filter Pack Filter Pack 50 Cerment 10.3 Sack Mix Image: Sa	Depth from Surface Feet to Feet Casing Type Material Casings Specificatons Wall Thickness (inches) Outside Diameter (inches) Screen Type 0 60 Blank PVC OD: 5.563 in. SDR: 21 Thickness: 0.265 in. 0.265 5.563 60 100 Screen PVC OD: 5.563 in. SDR: 21 Thickness: 0.265 in. 0.265 5.563 Milled Slots 100 110 Blank PVC OD: 5.563 in. SDR: 21 Thickness: 0.265 in. 0.265 5.563 Milled Slots 100 110 Blank PVC OD: 5.563 in. SDR: 21 Thickness: 0.265 in. 0.265 5.563 100 110 Blank PVC OD: 5.563 in. SDR: 21 Thickness: 0.265 in. 0.265 5.563 100 110 Blank PVC OD: 5.563 in. SDR: 21 Thickness: 0.265 0.265 5.563 130 Fill Fill Fill Fill Fill Fill 0bservations: 0 Certifications Certification S	Depth from Surface Feet to Feet Casing Type Material Casings Specificatons Wall Thickness (inches) Outside Diameter (inches) Screen Type Stot Size if any (inches) 0 60 Blank PVC OD: 5.563 in. SDR: 21 Thickness: 0.265 0.265 5.563 Image: constraint of the state of	Depth from Surface Feet to Feet Casing Type Material Casings Specificatons Wall Thickness (inches) Outside Diameter (inches) Screen Type Slot Size if any (inches) Descri (inches) 0 60 Blank PVC OD: 5.563 in. SDR: 21 Thickness: 0.265 in. 0.265 5.563 Image: Constraint of the state of th